

COMPOSITION

It is a semi-synthetic metal working fluid containing special synthetic esters, EP additives, corrosion inhibitors, antiwear, antioxidant additives and surfactants.

APPEARANCE

Clear, blue-green, light viscous fluid

pH(%5) : 9.0 – 9.5

Refractometer index : 1,3

PROPERTIES

MEGLUB YSB 02;

- Is a semi-synthetic metal working fluid containing 12 15 % mineral oil.
- Can be used all kind of machining operation like milling, drilling, turning, boring, grinding, etc.
- Contains EP, corrosion inhibition additives, boundary film and antiwear additives which improve tool/wheel performance during cutting and grinding operation.
- Has excellent corrosion resistance. (Is graded equal to 0° in accordance with DIN 51360 – 2.)
- Has high biostatic protection against microbiological contamination
- Has very long sump life.
- Provides rapid chip and swarf settling to maintain a clean system.
- Tramp oil separate from solution easily.

APPLICATION

The recommended concentration is % 5.

In order to obtain high productivity and hygiene, it is particularly recommended to disinfectate the system with Disinfectant in accordance with the instructions.

STORAGE

It should be stored in its original closed package and in protective places

PACKING

In 20-60 kg. plastic drums; 200 kg. barrels and 1000 kg IBC.