

<b>COMPOSITION</b>	Polydimethylsiloxane emulsion						
<b>IONIC TYPE</b>	Nonionic						
<b>APPEARANCE</b>	White, slightly viscous liquid						
<b>PROPERTIES</b>	<p>MEGSOL SKK 10 is a very effective antifoamer used in sizing, bleaching, dyeing, finishing baths and printing pastes.</p> <p>Can easily be diluted with soft water.</p> <p>Can be used together with anionic and cationic substances.</p> <p>Can be used in biological refineries with giving no harm to bacteria.</p> <p>Eliminates foam problem in preparing printing paste.</p>						
<b>APPLICATION</b>	<p>It should be diluted with soft water in ratio 1/5 – 1/10.</p> <p>If it is used in the diluted form, the daily solution should be mixed every time.</p> <p>The application amount is determined according to the foam formation of other chemicals.</p> <table><tr><td>Exhausting Process</td><td>0.03-0.10 g/l</td></tr><tr><td>Foulard</td><td>0.30- 0.60 g/l</td></tr><tr><td>In refinery</td><td>Diluted with water in a ratio 1/5</td></tr></table>	Exhausting Process	0.03-0.10 g/l	Foulard	0.30- 0.60 g/l	In refinery	Diluted with water in a ratio 1/5
Exhausting Process	0.03-0.10 g/l						
Foulard	0.30- 0.60 g/l						
In refinery	Diluted with water in a ratio 1/5						
<b>PACKING</b>	60 kg plastic drum and 200 kg barrel.						
<b>STORAGE</b>	It is advised to be stored in closed vessels. It must be protected from excessive cold and heat. Besides the lid of plastic drum has to be kept closed.						